

3.0SMCJ10A-AU ~ 3.0SMCJ220CA-AU Series

Surface Mount Transient Voltage Suppressor

Voltage

10~220 V

Power

3000 W



Features

- ISO10605(C=330 pF,R=330Ω): ± 30kV Air, ± 30kV Contact
- HBM $\geq \pm 8$ kV & CDM $\geq \pm 2$ kV
- AEC-Q101 qualified
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : Molded plastic, SMC
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.266 grams

SMC



Maximum Ratings and Thermal Characteristics (T_A = 25 °C unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNIT
Peak Pulse Power Dissipation(tp = 10 / 1000 us)	P _{PP} ⁽¹⁾	3000	W
Peak Forward Surge Current(8.3 ms single half sine-wave)	I _{FSM} ⁽³⁾	300	A
Peak Pulse Current on tp = 10 / 1000 us waveform(Fig.2)	I _{PPM} ⁽¹⁾	See table 1	A
ISO10605(C = 330 pF, R = 330 Ω) (Air)	V _{ESD}	±30	kV
ISO10605(C = 330 pF, R = 330 Ω) (Contact)		±30	
Typical Thermal Resistance Junction to Ambient	R _{θJA} ⁽²⁾	125	°C/W
Operating Junction Temperature Range	T _J	-55~150	°C
Storage Temperature Range	T _{STG}	-55~150	°C

3.0SMCJ10A-AU ~ 3.0SMCJ220CA-AU Series

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Part Number		V _{RWM}	V _{BR}			I _R		V _{C@I_{PP}}		Marking Code	
			Min.	Max.	I _T	@V _{RWM}	uA				
UNI.	BI.	V	V	V	mA	UNI.	BI.	V	A	UNI.	BI.
3000W Transient Voltage Suppressor											
3.0SMCJ10A-AU	3.0SMCJ10CA-AU	10	11.1	12.8	1	3	3	17	176.4	HDX	IDX
3.0SMCJ11A-AU	3.0SMCJ11CA-AU	11	12.2	14	1	3	3	18.2	164.8	HDZ	IDZ
3.0SMCJ12A-AU	3.0SMCJ12CA-AU	12	13.3	15.3	1	3	3	19.9	150.6	HEE	IEE
3.0SMCJ13A-AU	3.0SMCJ13CA-AU	13	14.4	16.5	1	3	3	21.5	139.4	HEG	IEG
3.0SMCJ14A-AU	3.0SMCJ14CA-AU	14	15.6	17.9	1	3	3	23.2	129.4	HEK	IEK
3.0SMCJ15A-AU	3.0SMCJ15CA-AU	15	16.7	19.2	1	3	3	24.4	123	HEM	IEM
3.0SMCJ16A-AU	3.0SMCJ16CA-AU	16	17.8	20.5	1	3	3	26	115.4	HEP	IEP
3.0SMCJ17A-AU	3.0SMCJ17CA-AU	17	18.9	21.7	1	3	3	27.6	106.6	HER	IER
3.0SMCJ18A-AU	3.0SMCJ18CA-AU	18	20	23.3	1	3	3	29.2	102.8	HET	IET
3.0SMCJ20A-AU	3.0SMCJ20CA-AU	20	22.2	25.5	1	3	3	32.4	92.6	HEV	IEV
3.0SMCJ22A-AU	3.0SMCJ22CA-AU	22	24.4	28	1	3	3	35.5	84.4	HEX	IEX
3.0SMCJ24A-AU	3.0SMCJ24CA-AU	24	26.7	30.7	1	3	3	38.9	77.2	HEZ	IEZ
3.0SMCJ26A-AU	3.0SMCJ26CA-AU	26	28.9	33.2	1	3	3	42.1	71.2	HFE	IFE
3.0SMCJ28A-AU	3.0SMCJ28CA-AU	28	31.1	35.8	1	3	3	45.4	66	HFG	IFG
3.0SMCJ30A-AU	3.0SMCJ30CA-AU	30	33.3	38.3	1	3	3	48.4	62	HFK	IFK
3.0SMCJ33A-AU	3.0SMCJ33CA-AU	33	36.7	42.2	1	3	3	53.3	56.2	HFM	IFM
3.0SMCJ36A-AU	3.0SMCJ36CA-AU	36	40	46	1	3	3	58.1	51.6	HFP	IFP
3.0SMCJ40A-AU	3.0SMCJ40CA-AU	40	44.4	51.1	1	3	3	64.5	46.4	HFR	IFR
3.0SMCJ43A-AU	3.0SMCJ43CA-AU	43	47.8	54.9	1	3	3	69.4	43.2	HFT	IFT
3.0SMCJ45A-AU	3.0SMCJ45CA-AU	45	50	57.5	1	3	3	72.7	41.2	HFV	IFV
3.0SMCJ48A-AU	3.0SMCJ48CA-AU	48	53.3	61.3	1	3	3	77.4	38.8	HFX	IFX
3.0SMCJ51A-AU	3.0SMCJ51CA-AU	51	56.7	65.2	1	3	3	82.4	36.4	HFZ	IFZ
3.0SMCJ54A-AU	3.0SMCJ54CA-AU	54	60	69	1	3	3	87.1	34.4	HGE	IGE
3.0SMCJ58A-AU	3.0SMCJ58CA-AU	58	64.4	74.1	1	3	3	93.6	32	HGG	IGG
3.0SMCJ60A-AU	3.0SMCJ60CA-AU	60	66.7	76.7	1	3	3	96.8	31	HGK	IGK
3.0SMCJ64A-AU	3.0SMCJ64CA-AU	64	71.1	81.8	1	3	3	103	29.2	HGM	IGM
3.0SMCJ70A-AU	3.0SMCJ70CA-AU	70	77.8	89.5	1	3	3	113	26.6	HGP	IGP

Note :

1. Non-repetitive current pulse, per Fig.3 and derated above $T_A=25^\circ\text{C}$ per Fig.2.
2. Mounted on a FR4 PCB, single-sided copper, mini pad.
3. Measured on 8.3ms single half sine wave or equivalent square wave for unidirectional device only, duty cycle=4 per minute maximum.

3.0SMCJ10A-AU ~ 3.0SMCJ220CA-AU Series

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)





Part Number		V _{RWM}	V _{BR}			I _R		V _{C@I_{PP}}		Marking Code	
			Min.	Max.	I _T	@V _{RWM}	uA				
UNI.	BI.	V	V	V	mA	UNI.	BI.	V	A	UNI.	BI.
3000W Transient Voltage Suppressor											
3.0SMCJ75A-AU	3.0SMCJ75CA-AU	75	83.3	95.8	1	3	3	121	24.8	HGR	IGR
3.0SMCJ78A-AU	3.0SMCJ78CA-AU	78	86.7	99.7	1	3	3	126	22.8	HGT	IGT
3.0SMCJ85A-AU	3.0SMCJ85CA-AU	85	94.4	108.2	1	3	3	137	20.8	HGV	IGV
3.0SMCJ90A-AU	3.0SMCJ90CA-AU	90	100	115.5	1	3	3	146	20.6	HGX	IGX
3.0SMCJ100A-AU	3.0SMCJ100CA-AU	100	111	128	1	3	3	162	18.6	HGZ	IGZ
3.0SMCJ110A-AU	3.0SMCJ110CA-AU	110	122	140.5	1	3	3	177	16.8	HHE	IHE
3.0SMCJ120A-AU	3.0SMCJ120CA-AU	120	133	153	1	3	3	193	15.6	HHG	IHG
3.0SMCJ130A-AU	3.0SMCJ130CA-AU	130	144	165.5	1	3	3	209	14.4	HHK	IHK
3.0SMCJ150A-AU	3.0SMCJ150CA-AU	150	167	192.5	1	3	3	243	12.4	HHM	IHM
3.0SMCJ160A-AU	3.0SMCJ160CA-AU	160	178	205	1	3	3	259	11.6	HHP	IHP
3.0SMCJ170A-AU	3.0SMCJ170CA-AU	170	189	217.5	1	3	3	275	11	HHR	IHR
3.0SMCJ180A-AU	3.0SMCJ180CA-AU	180	198	230.4	1	3	3	292	10.3	HHT	IHT
3.0SMCJ190A-AU	3.0SMCJ190CA-AU	190	209	243.2	1	3	3	308	9.7	HHV	IHV
3.0SMCJ200A-AU	3.0SMCJ200CA-AU	200	220	256	1	3	3	324	9.3	HHX	IHX
3.0SMCJ210A-AU	3.0SMCJ210CA-AU	210	231	268.8	1	3	3	340	8.8	HHZ	IHZ
3.0SMCJ220A-AU	3.0SMCJ220CA-AU	220	242	281.6	1	3	3	356	8.4	HIE	IIE

Note :

1. Non-repetitive current pulse, per Fig.3 and derated above $T_A=25^\circ\text{C}$ per Fig.2.
2. Mounted on a FR4 PCB, single-sided copper, mini pad.
3. Measured on 8.3ms single half sine wave or equivalent square wave for unidirectional device only, duty cycle=4 per minute maximum.

3.0SMCJ10A-AU ~ 3.0SMCJ220CA-AU Series

TYPICAL CHARACTERISTIC CURVES




3.0SMCJ10A-AU ~ 3.0SMCJ220CA-AU Series

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
3.0SMCJxxxxA-AU	SMC	0.8K pcs / 7" reel	See Table

Packaging Information & Mounting Pad Layout



3.0SMCJ10A-AU ~ 3.0SMCJ220CA-AU Series

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from PANJIT International Inc..
- PANJIT International Inc. reserves the rights to make changes of the content herein the document follow PCN procedure. Please refer to our website for the latest document.
- PANJIT International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- PANJIT International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. PANJIT International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed or authorized for equipment relating to human life, life-saving or life-sustaining applications, such as medical instruments and aerospace machinery, or for other applications intended to cause personal injury. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify PANJIT International Inc. for any damages resulting from such improper use or sale. For additional terms and conditions regarding the use of PANJIT products, please refer to the Terms of Use available on the PANJIT website.
- Since PANJIT uses lot number as the tracking base, please provide the lot number for tracking when complaining.