

**100V N-Channel Enhancement Mode MOSFET**

<b>Voltage</b>	<b>100 V</b>	<b>R<sub>DS(ON)</sub></b>	<b>28 mΩ</b>
<b>Current</b>	<b>22 A</b>	<b>Q<sub>G</sub> (TYP)</b>	<b>9.2 nC</b>

**Feature**


- R<sub>DS(ON)</sub> < 28 mΩ at V<sub>GS</sub> = 10 V, I<sub>D</sub> = 10 A
- R<sub>DS(ON)</sub> < 39 mΩ at V<sub>GS</sub> = 4.5 V, I<sub>D</sub> = 5 A
- High switching speed
- Low reverse transfer capacitance
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard
- 100% UIS / Rg test in mass production

**Mechanical Data**

- Case: DFN3333-8L Package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.03 grams

**Application**

- LED Headlight / PSE



**Absolute Maximum Ratings** (T<sub>A</sub> = 25 °C unless otherwise specified)

PARAMETER		SYMBOL	LIMIT	UNITS
Drain-Source Voltage		V <sub>DS</sub>	100	V
Gate-Source Voltage		V <sub>GS</sub>	±20	
Continuous Drain Current (Note 3)	T <sub>C</sub> =25 °C	I <sub>D</sub>	22	A
	T <sub>C</sub> =100 °C		16	
Pulsed Drain Current		I <sub>DM</sub>	88	A
Single Pulse Avalanche Current (Note 5)		I <sub>AS</sub>	6.3	A
Single Pulse Avalanche Energy (Note 5)		E <sub>AS</sub>	4.5	mJ
Power Dissipation	T <sub>C</sub> =25 °C	P <sub>D</sub>	30.6	W
	T <sub>C</sub> =100 °C		15.3	
Operating Junction and Storage Temperature Range		T <sub>J</sub> , T <sub>STG</sub>	-55~175	°C

**Thermal Characteristics**

PARAMETER	SYMBOL	VALUES			UNITS	
		MIN.	TYP.	MAX.		
Thermal Resistance	Junction-to-Case (Bottom)	R <sub>θJC</sub>	-	3.3	4.9	°C/W
	Junction-to-Ambient (Note 4)	R <sub>θJA</sub>	-	60	75	°C/W

**Electrical Characteristics** ( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
<b>Static Characteristics</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0\text{ V}, I_D=250\text{ }\mu\text{A}$	100	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=37\text{ }\mu\text{A}$	1.1	1.7	2.3	
Drain-Source On-State Resistance (Note 1)	$R_{DS(on)}$	$V_{GS}=10\text{ V}, I_D=10\text{ A}$	-	24	28	m $\Omega$
		$V_{GS}=4.5\text{ V}, I_D=5\text{ A}$	-	30	39	
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=100\text{ V}, V_{GS}=0\text{ V}$	-	-	1	$\mu\text{A}$
Gate-Source Leakage Current	$I_{GSS}$	$V_{GS}=\pm 20\text{ V}, V_{DS}=0\text{ V}$	-	-	$\pm 100$	nA
Transfer characteristics (Note 1)	$g_{fs}$	$V_{DS}=10\text{ V}, I_D=10\text{ A}$	-	24	-	S
<b>Dynamic Characteristics</b> (Note 6)						
Total Gate Charge	$Q_g$	$V_{DS}=50\text{ V}, I_D=10\text{ A}, V_{GS}=4.5\text{ V}$	-	4.4	-	nC
		$V_{DS}=50\text{ V}, I_D=10\text{ A}, V_{GS}=10\text{ V}$	-	9.2	12	nC
Gate-Source Charge	$Q_{gs}$		-	2.2	-	
Gate-Drain Charge	$Q_{gd}$		-	1.1	-	
Gate Plateau Voltage	$V_{plateau}$		-	3.3	-	V
Input Capacitance	$C_{iss}$	$V_{DS}=50\text{ V}, V_{GS}=0\text{ V}, f=250\text{ kHz}$	-	546	710	pF
Output Capacitance	$C_{oss}$		-	206	270	
Reverse Transfer Capacitance	$C_{riss}$		-	6.3	-	
Output Charge	$Q_{oss}$	$V_{DS}=50\text{ V}, V_{GS}=0\text{ V}$	-	15	20	nC
Turn-On Delay Time	$t_{d(on)}$	$V_{DD}=50\text{ V}, I_D=5\text{ A}, V_{GS}=10\text{ V}, R_G=1.6\text{ }\Omega$ (Note 2)	-	3.7	-	ns
Rise Time	$t_r$		-	1.6	-	
Turn-Off Delay Time	$t_{d(off)}$		-	9.6	-	
Fall Time	$t_f$		-	2.2	-	
Gate Resistance	$R_g$	$f=1.0\text{ MHz}$	-	1.05	2.1	$\Omega$
<b>Drain-Source Diode</b>						
Diode Forward Voltage	$V_{SD}$	$I_S=10\text{ A}, V_{GS}=0\text{ V}$	-	0.9	1.2	V
Reverse Recovery Charge	$Q_{rr}$	$I_F=5\text{ A}, V_{DD}=50\text{ V}, di/dt=100\text{ A}/\mu\text{s}$	-	32	-	nC
Reverse Recovery Time	$T_{rr}$		-	35	-	ns

NOTES :

1. Pulse width  $\leq 300\text{ }\mu\text{s}$ , Duty cycle  $\leq 2\%$ .
2. Essentially independent of operating temperature typical characteristics.
3. The maximum drain current calculated by maximum junction temperature and thermal impedance. It can be varied by application and environment.
4.  $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. Mounted on a 1 inch<sup>2</sup> with 2oz. square pad of copper.
5.  $E_{AS}$  is calculated based on the condition of  $L = 1.0\text{ mH}$ ,  $I_{AS} = 3.5\text{ A}$ ,  $V_{DD} = 50\text{ V}$ ,  $V_{GS} = 10\text{ V}$ . 100% test at  $L = 0.1\text{ mH}$ ,  $I_{AS} = 6.3\text{ A}$  in production.
6. Guaranteed by design, not subject to production testing.

TYPICAL CHARACTERISTIC CURVES




Fig.1 Output Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction temperature




Fig.5 Capacitance vs. Drain-Source Voltage




Fig.6 On-Resistance vs. Gate-Source Voltage

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Breakdown Voltage Variation vs. Temperature




Fig.9 Threshold Voltage Variation with Temperature




Fig.10 Source-Drain Diode Forward Voltage




Fig.11 Maximum Safe Operating Area





Fig.12 Normalized Transient Thermal Impedance

**Product and Packing Information**

Part No.	Package Type	Packing Type	Marking
PSMQB280N10LS2	DFN3333-8L	5000pcs / 13" reel	280GL2

**Packaging Information & Mounting Pad Layout**



**Marking Diagram**



- Y** = Year Code
- W** = Week Code (A~Z)
- L** = Lot Code (0~9)

## Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc.
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.