

## 100V N-Channel Enhancement Mode MOSFET

<b>Voltage</b>	<b>100 V</b>	<b><math>R_{DS(ON),max}</math></b>	<b>&lt; 5.0 m<math>\Omega</math></b>
<b>Current</b>	<b>120 A</b>	<b><math>Q_G</math> (TYP)</b>	<b>40.5 nC</b>

### Feature


- $R_{DS(ON),max}$  < 5.0 m $\Omega$  at  $V_{GS} = 10$  V,  $I_D = 50$  A
- $R_{DS(ON),max}$  < 7.0 m $\Omega$  at  $V_{GS} = 6$  V,  $I_D = 25$  A
- High switching speed
- Low reverse transfer capacitance
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

### Mechanical Data

- Case: TO-263 package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 1.38 grams

### Application

- SR solutions of Power supply, BMS, BLDC motor driver switch.



## Absolute Maximum Ratings ( $T_A = 25$ °C unless otherwise specified)

PARAMETER		SYMBOL	LIMIT	UNITS
Drain-Source Voltage		$V_{DS}$	100	V
Gate-Source Voltage		$V_{GS}$	$\pm 20$	
Continuous Drain Current (Note 3)	$T_C = 25$ °C	$I_D$	120	A
	$T_C = 100$ °C		76	
Pulsed Drain Current (Note 6)		$I_{DM}$	480	A
Single Pulse Avalanche Current (Note 5)		$I_{AS}$	50	A
Single Pulse Avalanche Energy (Note 5)		$E_{AS}$	318	mJ
Power Dissipation	$T_C = 25$ °C	$P_D$	138	W
	$T_C = 100$ °C		55	
Operating Junction and Storage Temperature Range		$T_J, T_{STG}$	-55~150	°C

### Thermal Characteristics

PARAMETER		SYMBOL	MAXIMUM	UNITS
Thermal Resistance	Junction-to-Case (Bottom)	$R_{\theta JC}$	0.9	°C/W
	Junction-to-Ambient (Note.4)	$R_{\theta JA}$	60	°C/W

## Electrical Characteristics (T<sub>A</sub> = 25 °C unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
<b>Static</b>						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	V <sub>GS</sub> =0 V, I <sub>D</sub> =250 μA	100	-	-	V
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =270 μA	1.8	2.8	3.8	
Drain-Source On-State Resistance (Note 1)	R <sub>DS(on)</sub>	V <sub>GS</sub> =10 V, I <sub>D</sub> =50 A	-	4.3	5.0	mΩ
		V <sub>GS</sub> =6 V, I <sub>D</sub> =25 A	-	5.4	7.0	
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> =100 V, V <sub>GS</sub> =0 V	-	-	1	μA
Gate-Source Leakage Current	I <sub>GSS</sub>	V <sub>GS</sub> =±20 V, V <sub>DS</sub> =0 V	-	-	±100	nA
Transfer characteristics (Note 1)	g <sub>fs</sub>	V <sub>DS</sub> =10 V, I <sub>D</sub> =50 A	-	100	-	S
Gate Resistance	R <sub>g</sub>	f =1.0 MHz	-	0.8	1.6	Ω
<b>Dynamic</b> (Note 6)						
Total Gate Charge	Q <sub>g</sub>	V <sub>DS</sub> =50 V, I <sub>D</sub> =50 A, V <sub>GS</sub> =10 V	-	40.5	53	nC
Gate-Source Charge	Q <sub>gs</sub>		-	15	-	
Gate-Drain Charge	Q <sub>gd</sub>		-	6	-	
Gate Plateau Voltage	V <sub>plateau</sub>		-	5	-	V
Input Capacitance	C <sub>iss</sub>	V <sub>DS</sub> =50 V, V <sub>GS</sub> =0 V, f=250 kHz	-	3010	3910	pF
Output Capacitance	C <sub>oss</sub>		-	1080	1400	
Reverse Transfer Capacitance	C <sub>rss</sub>		-	14	-	
Output Charge	Q <sub>oss</sub>	V <sub>DS</sub> =50 V, V <sub>GS</sub> =0 V	-	85	110	nC
Turn-On Delay Time	t <sub>d(on)</sub>	V <sub>DD</sub> =50 V, I <sub>D</sub> =50 A, V <sub>GS</sub> =10 V, R <sub>G</sub> =3.0 Ω (Note 2)	-	16	-	ns
Rise Time	t <sub>r</sub>		-	6	-	
Turn-Off Delay Time	t <sub>d(off)</sub>		-	25	-	
Fall Time	t <sub>f</sub>		-	6	-	
<b>Drain-Source Diode</b>						
Diode Forward Voltage	V <sub>SD</sub>	I <sub>S</sub> =50 A, V <sub>GS</sub> =0 V	-	0.9	1.2	V
Reverse Recovery Charge (Note 6)	Q <sub>rr</sub>	I <sub>F</sub> =50 A, V <sub>DD</sub> =50 V di/dt=100 A/μs	-	85	170	nC
Reverse Recovery Time (Note 6)	T <sub>rr</sub>		-	56	112	ns

### NOTES :

- Pulse width  $\leq 300 \mu\text{s}$ , Duty cycle  $\leq 2 \%$
- Essentially independent of operating temperature typical characteristics.
- The maximum drain current calculated by maximum junction temperature and thermal impedance. It can be varied by application and environment.
- R<sub>θJA</sub> is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. Mounted on a 1 inch<sup>2</sup> with 2oz.square pad of copper.
- E<sub>AS</sub> is calculated based on the condition of L = 1.0 mH, I<sub>AS</sub> = 25.2 A, V<sub>DD</sub> = 50 V, V<sub>GS</sub> = 10 V. 100% test at L = 0.1 mH, I<sub>AS</sub> = 50 A in production.
- Guaranteed by design, not subject to production testing.

TYPICAL CHARACTERISTIC CURVES




Fig.1 Output Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction temperature




Fig.5 Capacitance vs. Drain-Source Voltage




Fig.6 On-Resistance vs. Gate-Source Voltage

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Breakdown Voltage Variation vs. Temperature




Fig.9 Threshold Voltage Variation with Temperature




Fig.10 Source-Drain Diode Forward Voltage




Fig.11 Maximum Safe Operating Area




Fig.12 Normalized Transient Thermal Impedance

TYPICAL CHARACTERISTIC CURVES




Fig.13 Avalanche Characteristics





Fig.14 Drain Current vs. Case Temperature


**Product and Packing Information**

Part No.	Package Type	Packing Type	Marking
PSMB050N10NS2	TO-263	50pcs / Tube 800pcs / Reel	050N10NS

**Packaging Information & Mounting Pad Layout**



**Marking Diagram**



- Y** = Year Code
- W** = Week Code (A~Z)
- LL** = Lot Code (00~99)
- x** = Production Line Code

## Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.