

**80V N-Channel Enhancement Mode MOSFET**

<b>Voltage</b>	<b>80 V</b>	<b>R<sub>DS(ON)</sub></b>	<b>3.4 mΩ</b>
<b>Current</b>	<b>166 A</b>	<b>Q<sub>G</sub> (TYP)</b>	<b>103.5 nC</b>

**Feature:**


- R<sub>DS(ON)</sub> Max, V<sub>GS</sub>@10V, I<sub>D</sub>@50A<3.4mΩ
- R<sub>DS(ON)</sub> Max, V<sub>GS</sub>@7V, I<sub>D</sub>@25A<5mΩ
- 100% Avalanche Tested
- 100% Rg Tested
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

**Mechanical Data**

- Case: TO-220AB-L package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 2.0948 grams

**Application**

- BMS, BLDC, SMPS SR.



**Absolute Maximum Ratings** (T<sub>A</sub> = 25 °C unless otherwise specified)

PARAMETER	SYMBOL	LIMIT	UNITS	
Drain-Source Voltage	V <sub>DS</sub>	80	V	
Gate-Source Voltage	V <sub>GS</sub>	±20		
Continuous Drain Current	I <sub>D</sub>	T <sub>C</sub> =25°C (Note 3)	166	A
		T <sub>C</sub> =100°C	117	
Pulsed Drain Current	I <sub>DM</sub>	480	A	
Single Pulse Avalanche Current (Note 5)	I <sub>AS</sub>	38	A	
Single Pulse Avalanche Energy (Note 5)	E <sub>AS</sub>	722	mJ	
Power Dissipation	P <sub>D</sub>	T <sub>C</sub> =25°C	156	W
		T <sub>C</sub> =100°C	62.5	
Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55~175	°C	

**Thermal Characteristics**

PARAMETER	SYMBOL	MAXIMUM	UNITS
Thermal Resistance	Junction-to-Case	0.8	°C/W
	Junction-to-Ambient (Note 4)	62.5	°C/W

**Electrical Characteristics** ( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
<b>Static</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$ (Note 7)	$V_{GS}=0V, I_D=250\mu A$	80	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	2.25	3.2	3.75	
Drain-Source On-State Resistance (Note 1)	$R_{DS(on)}$	$V_{GS}=10V, I_D=50A$	-	3	3.4	m $\Omega$
		$V_{GS}=7V, I_D=25A$	-	3.5	5	
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=80V, V_{GS}=0V$	-	-	1	$\mu A$
Gate-Source Leakage Current	$I_{GSS}$	$V_{GS}=\pm 20V, V_{DS}=0V$	-	-	$\pm 100$	nA
<b>Dynamic</b> (Note 6)						
Total Gate Charge	$Q_g$	$V_{DS}=40V, I_D=50A,$ $V_{GS}=7V$	-	76	-	nC
		$V_{DS}=40V, I_D=50A,$ $V_{GS}=10V$	-	103.5	-	
Gate-Source Charge	$Q_{gs}$		-	34.1	-	
Gate-Drain Charge	$Q_{gd}$	-	20.9	-		
Input Capacitance	$C_{iss}$	$V_{DS}=40V, V_{GS}=0V,$ $F=1MHz$	-	7430	-	pF
Output Capacitance	$C_{oss}$		-	1483	-	
Reverse Transfer Capacitance	$C_{rss}$		-	89	-	
Turn-On Delay Time	$t_{d(on)}$		-	70.6	-	
Turn-On Rise Time	$t_r$	$V_{DD}=40V, I_D=50A,$ $V_{GS}=10V, R_G=2\Omega$ (Note 2)	-	103	-	ns
Turn-Off Delay Time	$t_{d(off)}$		-	122	-	
Turn-Off Fall Time	$t_f$		-	48.5	-	
Gate Resistance	$R_g$	$f=1.0MHz$	-	3.2	-	
<b>Drain-Source Diode</b>						
Diode Forward Voltage	$V_{SD}$	$I_S=50A, V_{GS}=0V$	-	0.88	1.2	V
Reverse Recovery Charge	$Q_{rr}$	$I_S=50A$	-	114	-	nC
Reverse Recovery Time	$T_{rr}$	$di/dt=100A/\mu s$	-	69	-	ns

NOTES :

1. Pulse width < 580 $\mu s$ ,
2. Essentially independent of operating temperature typical characteristics.
3. The maximum current rating is silicon limited.
4.  $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. Mounted on a 1 inch<sup>2</sup> with 2oz. square pad of copper.
5. The test condition is  $L=1mH, I_{AS}=38A, V_{DD}=40V, V_{GS}=10V, R_G=25\Omega$ , Starting  $T_J=25\text{ }^\circ\text{C}$
6. Guaranteed by design, not subject to production testing.
7.  $BV_{DSS}$  is over 85V during mass production.

TYPICAL CHARACTERISTIC CURVES




Fig.1 Output Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction Temperature




Fig.5 Capacitance vs. Drain-Source Voltage




Fig.6 On-Resistance vs. Gate-Source Voltage

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Breakdown Voltage Variation vs. Temperature




Fig.9 Threshold Voltage Variation with Temperature




Fig.10 Source-Drain Diode Forward Voltage




Fig.11 Maximum Safe Operating Area




Fig.12 Normalized Transient Thermal Impedance

TYPICAL CHARACTERISTIC CURVES





Fig.13 Drain Current vs. Case Temperature


**Product and Packing Information**

Part No.	Package Type	Packing Type	Marking
PSMP032N08NS1	TO-220AB-L	50pcs / Tube	032N08NS

**Packaging Information**



**Marking Diagram**



## Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.