

PE4503C2A-AU ~ PE4536C2A-AU Series

ESD Protection

Voltage

3.3~36 V



Features

- ISO10605(C=330pF, R=330Ω) : ±30kV Air, ±30kV Contact
- HBM ≥ ±8KV & CDM ≥ ±2KV
- IEC61000-4-5(Lightning) : 6~37.8A(8/20uS)
- AEC-Q101 qualified
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : SOT-23 Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.0084 grams

SOT-23



Maximum Ratings and Thermal Characteristics (T_A = 25 °C unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNITS
ESD IEC61000-4-2(Air)	V _{ESD}	±30	kV
ESD IEC61000-4-2(Contact)		±30	
Typical Thermal Resistance ^(Note 1)	R _{θJA}	350	°C/W
Operating Junction Temperature Range	T _J	-55~150	°C
Storage Temperature Range	T _{STG}	-55~150	°C

PE4503C2A-AU ~ PE4536C2A-AU Series

Electrical Characteristics (T_A = 25 °C unless otherwise noted)

PE4503C2A-AU						
PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V _{RWM}	-	-	-	3.3	V
Reverse Breakdown Voltage	V _{BR}	I _{BT} = 1mA	5	-	7	V
Reverse Leakage Current	I _R	V _R = 3.3V	-	-	1	uA
Clamping Voltage	V _C	I _{PP} = 37.8A, t _P = 8/20us	-	-	13	V
Off State Junction Capacitance	C _J	0Vdc Bias f = 1MHz	-	-	400	pF

PE4505C2A-AU						
PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V _{RWM}	-	-	-	5	V
Reverse Breakdown Voltage	V _{BR}	I _{BT} = 1mA	6	-	8	V
Reverse Leakage Current	I _R	V _R = 5V	-	-	1	uA
Clamping Voltage	V _C	I _{PP} = 31.2A, t _P = 8/20us	-	-	15	V
Off State Junction Capacitance	C _J	0Vdc Bias f = 1MHz	-	-	390	pF

PE4509C2A-AU						
PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V _{RWM}	-	-	-	9	V
Reverse Breakdown Voltage	V _{BR}	I _{BT} = 1mA	9.9	-	12	V
Reverse Leakage Current	I _R	V _R = 9V	-	-	0.5	uA
Clamping Voltage	V _C	I _{PP} = 20.4A, t _P = 8/20us	-	-	23	V
Off State Junction Capacitance	C _J	0Vdc Bias f = 1MHz	-	-	290	pF

PE4512C2A-AU						
PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V _{RWM}	-	-	-	12	V
Reverse Breakdown Voltage	V _{BR}	I _{BT} = 1mA	13.2	-	15.5	V
Reverse Leakage Current	I _R	V _R = 12V	-	-	0.1	uA
Clamping Voltage	V _C	I _{PP} = 17.4A, t _P = 8/20us	-	-	26.5	V
Off State Junction Capacitance	C _J	0Vdc Bias f = 1MHz	-	-	195	pF

PE4503C2A-AU ~ PE4536C2A-AU Series

PE4515C2A-AU						
PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V_{RWM}	-	-	-	15	V
Reverse Breakdown Voltage	V_{BR}	$I_{BT} = 1\text{mA}$	16.5	-	19.5	V
Reverse Leakage Current	I_R	$V_R = 15\text{V}$	-	-	0.1	μA
Clamping Voltage	V_C	$I_{PP} = 13.2\text{A}$, $t_P = 8/20\mu\text{s}$	-	-	35.5	V
Off State Junction Capacitance	C_J	0Vdc Bias $f = 1\text{MHz}$	-	-	127	pF

PE4524C2A-AU						
PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V_{RWM}	-	-	-	24	V
Reverse Breakdown Voltage	V_{BR}	$I_{BT} = 1\text{mA}$	26.4	-	31	V
Reverse Leakage Current	I_R	$V_R = 24\text{V}$	-	-	0.1	μA
Clamping Voltage	V_C	$I_{PP} = 8.4\text{A}$, $t_P = 8/20\mu\text{s}$	-	-	55	V
Off State Junction Capacitance	C_J	0Vdc Bias $f = 1\text{MHz}$	-	-	82.5	pF

PE4536C2A-AU						
PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Reverse Stand-Off Voltage ^(Note 2)	V_{RWM}	-	-	-	36	V
Reverse Breakdown Voltage	V_{BR}	$I_{BT} = 1\text{mA}$	39.6	-	46.5	V
Reverse Leakage Current	I_R	$V_R = 36\text{V}$	-	-	0.1	μA
Clamping Voltage	V_C	$I_{PP} = 6\text{A}$, $t_P = 8/20\mu\text{s}$	-	-	67.5	V
Off State Junction Capacitance	C_J	0Vdc Bias $f = 1\text{MHz}$	-	-	60	pF

NOTES :

1. Mounted on a FR4 PCB, single-sided copper, standard footprint.
2. A transient suppressor is selected according to the working peak reverse voltage (V_{RWM}), which should be equal to or greater than the DC or continuous peak operation voltage level.

PE4503C2A-AU ~ PE4536C2A-AU Series

TYPICAL CHARACTERISTIC CURVES




Fig.1 Typical Peak Clamping Voltage




Fig.2 TLP Measurement




Fig.3 Pulse Waveform




Fig.4 Typical Junction Capacitance




Fig.5 Typical Reverse Characteristics





Fig.6 Typical Forward Characteristics

PE4503C2A-AU ~ PE4536C2A-AU Series

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
PE4503C2A-AU	SOT-23	3K pcs / 7" reel	AEG
PE4505C2A-AU	SOT-23	3K pcs / 7" reel	AEA
PE4509C2A-AU	SOT-23	3K pcs / 7" reel	AEB
PE4512C2A-AU	SOT-23	3K pcs / 7" reel	AEC
PE4515C2A-AU	SOT-23	3K pcs / 7" reel	AED
PE4524C2A-AU	SOT-23	3K pcs / 7" reel	AEE
PE4536C2A-AU	SOT-23	3K pcs / 7" reel	AEF

Packaging Information & Mounting Pad Layout



PE4503C2A-AU ~ PE4536C2A-AU Series

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.