

Speedy Diode - Short Reverse Recovery Time, Fast Recovery Diode

V_{RRM}	650 V	I_F	75 A
$V_{F(Typ.)}$	1.7 V	$T_{RR(TYP)}$	40 ns

Features

- Fast recovery
- Suppressed switching loss with low T_{RR}
- Soft recovery characteristic for better EMI
- High junction temperature 175 °C
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case: TO-247-2LD molded plastic
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 6.056 grams

Application

- PFC, UPS, PV Inverter

TO-247AD-2LD



Maximum Ratings and Thermal Characteristics ($T_C = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)

PARAMETER	SYMBOL	LIMIT	UNITS
Repetitive Peak Reverse Voltage	V_{RRM}	650	V
DC Blocking Voltage	V_{DC}	650	V
Diode Forward Current, $D=1$ @ $T_C=137^{\circ}\text{C}$	$I_{F(AV)}$	75	A
Repetitive Peak Surge Current $t_p = 8.3\text{ ms}$, sine-wave, $D=0.5$	I_{FRM}	420	A
Peak Forward Surge Current $t_p = 8.3\text{ ms}$, single half sine-wave	I_{FSM}	600	A
Peak Forward Surge Current $t_p = 10\text{ ms}$, single half sine-wave	I_{FSM}	540	A
Maximum I^2t for fusing ($t_p = 10\text{ ms}$)	I^2t	1458	A^2s
Maximum Power Dissipation	P_{total}	391	W
Operating Junction Temperature Range	T_J	-55~175	$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-55~175	$^{\circ}\text{C}$
Thermal Resistance	$R_{\theta JC}$	0.38	$^{\circ}\text{C/W}$
	$R_{\theta JA_typ}$	31	$^{\circ}\text{C/W}$

Electrical Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Forward voltage drop	V_F	$I_F = 75\text{ A}, T_J = 25^\circ\text{C}$	-	1.7	2.2	V
		$I_F = 75\text{ A}, T_J = 125^\circ\text{C}$	-	1.45	-	
		$I_F = 75\text{ A}, T_J = 150^\circ\text{C}$	-	1.38	-	
Reverse leakage current	I_R	$V_R = 650\text{ V}, T_J = 25^\circ\text{C}$	-	0.04	30	μA
		$V_R = 650\text{ V}, T_J = 125^\circ\text{C}$	-	21	-	
		$V_R = 650\text{ V}, T_J = 150^\circ\text{C}$	-	93	-	
Reverse recovery time	T_{RR}	$I_F = 0.5\text{ A}, I_R = 1\text{ A}, I_{RR} = 0.25\text{ A}$ $T_J = 25^\circ\text{C}$	-	53.2	-	ns
		$I_F = 1\text{ A}, V_R = 30\text{ V},$ $di/dt = 100\text{ A}/\mu\text{s},$ $T_J = 25^\circ\text{C}$	-	38	-	ns
Reverse recovery time	T_{RR}	$I_F = 75\text{ A}, V_R = 400\text{ V},$ $di/dt = 200\text{ A}/\mu\text{s},$ $T_J = 25^\circ\text{C}$	-	40	-	ns
Peak recovery current	I_{RRM}		-	4.1	-	A
Reverse recovery charge	Q_{RR}		-	100	-	nC
Softness factor = t_b / t_a	S		-	1	-	
Reverse recovery time	T_{RR}	$I_F = 75\text{ A}, V_R = 400\text{ V},$ $di/dt = 200\text{ A}/\mu\text{s},$ $T_J = 125^\circ\text{C}$	-	305	-	ns
Peak recovery current	I_{RRM}		-	10	-	A
Reverse recovery charge	Q_{RR}		-	1400	-	nC
Softness factor = t_b / t_a	S		-	5.6	-	
Reverse recovery time	T_{RR}	$I_F = 75\text{ A}, V_R = 400\text{ V},$ $di/dt = 1000\text{ A}/\mu\text{s},$ $T_J = 25^\circ\text{C}$	-	47	-	ns
Peak recovery current	I_{RRM}		-	18.1	-	A
Reverse recovery charge	Q_{RR}		-	442	-	nC
Softness factor = t_b / t_a	S		-	1.5	-	
Reverse recovery time	T_{RR}	$I_F = 75\text{ A}, V_R = 400\text{ V},$ $di/dt = 1000\text{ A}/\mu\text{s},$ $T_J = 125^\circ\text{C}$	-	165	-	ns
Peak recovery current	I_{RRM}		-	34.7	-	A
Reverse recovery charge	Q_{RR}		-	2963	-	nC
Softness factor = t_b / t_a	S		-	3.3	-	

TYPICAL CHARACTERISTIC CURVES




Fig.1 Forward Characteristics




Fig.2 Reverse Characteristics




Fig.3 Average Current Derating Curve




Fig.4 Peak Current Derating Curve




Fig.5 Typical Junction Capacitance




Fig.6 Typical Peak reverse recovery current versus di/dt




Fig.7 Typical Reverse Recovery Time Versus di/dt




Fig.8 Typical Reverse Recovery Charges Versus di/dt




Fig.9 Max. transient thermal impedance Junction to Case





Fig.10 Transient thermal impedance Junction to Ambient

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
PSDH7565S2	TO-247AD-2LD	30pcs / Tube	SDH7565S2

Packaging Information



Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document follow PCN procedure. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.