PJQ25818AW-AU

80V N-Channel Enhancement Mode MOSFET

Voltage	80 V	Current	14 A

DFN2020BW-6L



Features

- $R_{DS(ON)}$, V_{GS}@10V, I_D@3A<60mΩ
- $R_{DS(ON)}$, V_{GS}@4.5V, I_D@1.5A<82mΩ
- Excellent FOM
- Logic Level Drive
- Wettable flank terminals
- AEC-Q101 qualified
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : DFN2020BW-6L Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.0096 grams

Maximum Ratings and Thermal Characteristics (T_A=25°C unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNIT
Drain-Source Voltage		V_{DS}	80	V
Gate-Source Voltage		V_{GS}	±20	
Continuous Drain Current(Note 3)	T_C=25°C	I_D	14	A
	T_C=100°C		10	
Pulsed Drain Current(Note 1)	T_C=25°C	I_{DM}	26	
Power Dissipation	T_C=25°C	P_D	24	W
	T_C=100°C		12	
Continuous Drain Current(Note 4)	T_A=25°C	I_D	4.3	A
	T_A=70°C		3.6	
Power Dissipation	T_A=25°C	P_D	2.3	W
	T_A=70°C		1.6	
Operating Junction and Storage Temperature Range		T_J,T_{STG}	-55~175	°C
Thermal Resistance(Note 4)	Junction to Case	$R_{\theta JC}$	6.2	°C/W
	Junction to Ambient	$R_{\theta JA}$	65	

PJQ25818AW-AU

Electrical Characteristics (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V, I_D=250uA	80	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=250uA	1.2	2	3	V
Drain-Source On-State Resistance	$R_{DS(on)}$	V_{GS}=10V, I_D=3A	-	48	60	mΩ
		V_{GS}=4.5V, I_D=1.5A	-	63	82	mΩ
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=80V, V_{GS}=0V	-	-	1	uA
Gate-Source Leakage Current	I_{GSS}	V_{GS}=±20V, V_{DS}=0V	-	-	±100	nA
Dynamic(Note 5)						
Total Gate Charge	Q_g	V_{DS}=40V, I_D=3A, V_{GS}=10V (Note 2)	-	4	6	nC
Gate-Source Charge	Q_{gs}		-	1	-	nC
Gate-Drain Charge	Q_{gd}		-	0.7	-	nC
Input Capacitance	Ciss	V_{DS}=40V, V_{GS}=0V, f=1MHz	-	368	560	pF
Output Capacitance	Coss		-	177	270	pF
Reverse Transfer Capacitance	Crss		-	7	13	pF
Gate resistance	R_g	f=1MHz	-	2.3	-	Ω
Turn-On Delay Time	$td_{(on)}$	V_{DS}=40V, I_D=3A, V_{GS}=10V, R_G=3Ω (Note 2)	-	7	-	ns
Turn-On Rise Time	t_r		-	6.5	-	ns
Turn-Off Delay Time	$td_{(off)}$		-	7	-	ns
Turn-Off Fall Time	t_f		-	4	-	ns
Drain-Source Diode						
Diode Forward Current	I_S	T_C=25°C (Package Limit)	-	-	14	A
Pulsed Diode Forward Current	I_{SM}		-	-	26	A
Diode Forward Voltage	V_{SD}	I_S=3A, V_{GS}=0V	-	0.86	1.3	V
Reverse Recovery Time	Trr	V_{DD}=40V,V_{GS}=0V, I_S=3A,dI_S/dt=100A/us	-	26	-	ns
Reverse Recovery Charge	Qrr		-	18	-	nC

NOTES :

1. Pulse width≤300us, Duty cycle≤2%.
2. Essentially independent of operating temperature typical characteristics.
3. Chip capability with an $R_{\theta JC}$=6.2°C/W.
4. $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. Mounted on a 1 inch^2 with 2oz.square pad of copper.
5. Guaranteed by design, not subject to production testing.

PJQ25818AW-AU

TYPICAL CHARACTERISTIC CURVES



Fig.1 On-Region Characteristics



Fig.2 Transfer Characteristics



Fig.3 On-Resistance vs. Drain Current



Fig.4 On-Resistance vs. Junction temperature



Fig.5 On-Resistance Variation with V_{GS}



Fig.6 Source-Drain Diode Forward Voltage

PJQ25818AW-AU

TYPICAL CHARACTERISTIC CURVES



Fig.7 Gate-Charge Characteristics



Fig.8 Breakdown Voltage Variation vs. Temperature



Fig.9 Threshold Voltage Variation with Temperature



Fig.10 Capacitance vs. Drain-Source Voltage



Fig.11 Maximum Safe Operating Area



Fig.12 Normalized Transient Thermal Impedance

PJQ25818AW-AU

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
PJQ25818AW-AU	DFN2020BW-6L	3K pcs / 7” reel	L88

Packaging Information & Mounting Pad Layout

DFN2020BW-6L Dimension **Unit: inch(mm)**



DFN2020BW-6L Pad Layout **Unit: inch(mm)**



Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document follow PCN procedure. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.