

Surface Mount Super Fast Recovery Rectifiers

V_{RRM}

200~600V

I_F

8 A


Features

- Superfast recovery times-epitaxial.
- Low forward voltage , high current capability.
- Exceeds environmental standards of MIL-S-19500/228
- Hermetically sealed.
- Low leakage.
- High surge capability.
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case: TO-252AA molded plastic
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.3217 grams

TO-252AA



Maximum Ratings and Thermal Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise specified)

PARAMETER		SYMBOL	ED802CD	ED803CD	ED804CD	ED806CD	UNIT
Maximum Repetitive Peak Reverse Voltage		V _{RRM}	200	300	400	600	V
Maximum rms voltage		V _{RMS}	140	210	280	420	V
Maximum DC Blocking Voltage		V _{DC}	200	300	400	600	V
Maximum average Forward rectified Current		I _{F(AV)}	8				A
Peak Forward Surge Current <i>tp = 8.3 ms, single half sine-wave</i>		I _{FSM}	85				A
Maximum Forward voltage at 4A per diode (Note 1)		V _F	0.95	1.3		1.7	V
Maximum dc reverse current at rated dc blocking voltage	T _J =25 °C	I _R	1				μA
	T _J =125 °C		300				
Maximum reverse recovery time (Note 2)		T _{RR}	35				nS
Typical thermal resistance	(Note 3)	R _{θJA}	50				°C/W
	(Note 4)	R _{θJL}	10				
	(Note 4)	R _{θJC}	12				
Operating Junction and Storage Temperature Range		T _{STG}	-55~150				°C

NOTES :

1. Pulse Test with $PW=300\ \mu\text{sec}$, 2% Duty Cycle.
2. Reverse Recovery Tset Conditions: $I_F=0.5\text{A}$, $I_R=1\text{A}$, $I_{rr}=0.25\text{A}$.
3. Mounted on a FR4 PCB, single-sided copper, standard footprint.
4. Mounted on a FR4 PCB, single-sided copper, with 100 cm² copper pad area.

TYPICAL CHARACTERISTIC CURVES




Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics






Fig.4 Typical Forward Characteristics

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
ED802CD	TO-252AA	3,000 pcs / 13" reel	ED802CD
ED803CD	TO-252AA	3,000 pcs / 13" reel	ED803CD
ED804CD	TO-252AA	3,000 pcs / 13" reel	ED804CD
ED806CD	TO-252AA	3,000 pcs / 13" reel	ED806CD

Packaging Information & Mounting Pad Layout



Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from PANJIT International Inc..
- PANJIT International Inc. reserves the rights to make changes of the content herein the document follow PCN procedure. Please refer to our website for the latest document.
- PANJIT International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- PANJIT International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. PANJIT International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed or authorized for equipment relating to human life, life-saving or life-sustaining applications, such as medical instruments, transportation equipment, aerospace machinery, or for other applications intended to cause personal injury. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify PANJIT International Inc. for any damages resulting from such improper use or sale. For additional terms and conditions regarding the use of PANJIT products, please refer to the Terms of Use available on the PANJIT website.
- Since PANJIT uses lot number as the tracking base, please provide the lot number for tracking when complaining.