

800V With High T_J Ultra Low V_F Bridge Rectifier

Voltage

800 V

Current

15A

Features



- Oxide planar chip junction
- Low forward voltage drop ($V_F@0.72V$)
- Low leakage current ($I_R@20uA$)
- Lead free in compliance with EU RoHS 2.0
- Halogen-free according to IEC 61249 standard


Mechanical Data

- Case : KBJ-2 Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 4.1442 grams

Application

- Computing Power / Desktop Power
- Game Console Power
- Server Power
- Air Conditioner out door power board
- High Power/High Efficiency Power
- Home Appliances Power Board

KBJ-2



Key Parameters	
Parameter	Value
V_{RRM}	800V
$I_F(AV)$	15A
I_{FSM}	220A
$V_F@175^{\circ}C$	0.72V
I_R	1uA
T_J max.	175$^{\circ}C$
Package	KBJ-2

Maximum Ratings and Thermal Characteristics ($T_A = 25\text{ }^{\circ}\text{C}$ unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNIT
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	800	V
Maximum RMS Voltage		V_{RMS}	560	V
Maximum DC Blocking Voltage		V_{DC}	800	V
Maximum Average Forward Current	With heatsink	$I_{F(AV)}$	15	A
	Without heatsink		4.7	
Peak Forward Surge Current : 8.3 ms Single Half Sine-Wave Superimposed On Rated Load	@ $T_A = 25\text{ }^{\circ}\text{C}$	I_{FSM}	220	A
	@ $T_A = 125\text{ }^{\circ}\text{C}$		176	
Peak Forward Surge Current : 1.0 ms Single Half Square -Wave Superimposed On Rated Load	@ $T_A = 25\text{ }^{\circ}\text{C}$	I_{FSM}	440	A
	@ $T_A = 125\text{ }^{\circ}\text{C}$		352	
$I^2 t$ rating for fusing ($t = 8.3\text{ms}$)		$I^2 t$	200	A^2S
Typical Junction Capacitance Measured at 1 MHZ And Applied $V_R = 4\text{ V}$		C_J	100	pF
Typical Thermal Resistance (Note 1) (with heatsink)	$R_{\theta JA}$		6	$^{\circ}\text{C/W}$
	$R_{\theta JL}$		4	
	$R_{\theta JC}$		1	
Operating junction and storage temperature range		T_J, T_{STG}	-55~175	$^{\circ}\text{C}$
Mounting torque @ Recommend torque:5Kg.cm		Tor	8	Kg.cm

Electrical Characteristics ($T_A = 25\text{ }^{\circ}\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Forward Voltage	V_F	$I_F = 7.5\text{ A}, T_J = 25\text{ }^{\circ}\text{C}$	-	0.88	0.92	V
		$I_F = 7.5\text{ A}, T_J = 125\text{ }^{\circ}\text{C}$	-	0.75	-	
Reverse Current	I_R	$V_R = 800\text{ V}, T_J = 25\text{ }^{\circ}\text{C}$	-	0.2	1	μA
		$V_R = 800\text{ V}, T_J = 125\text{ }^{\circ}\text{C}$	-	20	-	

NOTES :

1. Device mounted on 10 cm * 9.4 cm * 2.6 cm Fin type heat sink.

TYPICAL CHARACTERISTIC CURVES




Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics





Fig.4 Typical Forward Characteristics

Product and Packing Information

Part No.	Package Type	Packing Type	Marking
KBJ1508HULV	KBJ-2	20 pcs / tube	KBJ1508HULV

Packaging Information



Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from PANJIT International Inc..
- PANJIT International Inc. reserves the rights to make changes of the content herein the document follow PCN procedure. Please refer to our website for the latest document.
- PANJIT International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- PANJIT International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. PANJIT International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed or authorized for equipment relating to human life, life-saving or life-sustaining applications, such as medical instruments, transportation equipment, aerospace machinery, or for other applications intended to cause personal injury. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify PANJIT International Inc. for any damages resulting from such improper use or sale. For additional terms and conditions regarding the use of PANJIT products, please refer to the Terms of Use available on the PANJIT website.
- Since PANJIT uses lot number as the tracking base, please provide the lot number for tracking when complaining.